

NOMAPACK® SYSTEM



The frame for sensitive goods

NOMAPACK® System, the efficient transport protection for sensitive goods. Thanks to its directly extruded, specially developed L-shape with integrated holes, it offers ideal protection against impacts and vibration and is easy to process into a packaging frame.

- Outstanding protection against shocks and vibrations
- Tailor-made, adaptable and customer-oriented solutions

Product features:

- PE-LD foam
- Density from 24 kg/m³ to 34 kg/m³
- Supplied as lengths
- Water absorption < 1 – vol.% after 40 days
- Recyclable

Applications:

- High-tech products
- Medical devices




www.nmc.eu

NMC sa

Gert-Noël-Strasse – B-4731 Eynatten
 ☎ +32 87 85 85 00 – 📠 +32 87 85 85 11
info@nmc.eu



NOMAPACK® System



COLOUR	Standard blue
LENGTH	2.030 mm ±30 mm
PACKAGING	Lengths in boxes
BOXES ON PALLET	4
FEATURES	<ul style="list-style-type: none"> ■ For light goods ■ Specially suitable for sensitive surfaces ■ Easy to fix




m³ /  = 0,50

 2040 * 590 * 390 mm

Type	A	B	C	D	E	Packaging unit	Item Code
	mm	mm	mm	mm	mm	m	
30 mm	30 ±2	63 ±3	63 ±3	30 ±2	93° ±3	140	3002187
40 mm	40 ±2	85 ±3	85 ±3	40 ±2	93° ±3	84	3002189
50 mm	50 ±2	98 ±3	98 ±3	50 ±2	93° ±3	56	3002193

NOMAPACK® System HD



COLOUR	Standard blue
LENGTH	2.030 mm ±30 mm
PACKAGING	Lengths in boxes
BOXES ON PALLET	4
FEATURES	<ul style="list-style-type: none"> ■ For heavy goods ■ Specially suitable for sensitive surfaces ■ Easy to fix



m³ /  = 0,50

 2040 * 590 * 390 mm

Type	A	B	C	D	E	Packaging unit	Item Code
	mm	mm	mm	mm	mm	m	
20 mm	21 ±1	52 ±2	52 ±2	21 ±1	90° ±3	224	3002184
30 mm	30 ±2	63 ±3	63 ±3	30 ±1	90° ±3	140	3002186
40 mm	40 ±2	80 ±2	80 ±2	40 ±2	93° ±3	84	3002188
50 mm	50 ±2	97 ±3	97 ±3	50 ±1	93° ±3	56	3002192

NMC s.a. reserves the right to change or modify any of the technical data or size range of its products without prior notice. Slight changes and variations in colour, shape, design, dimension and weight are not seen as contract breach. The technical data contained in this brochure has been obtained under specific test conditions and the correct application of our products is the responsibility of the user. For questions about technical details please contact your sales representatives. Partial impression or reprint is only allowed with our explicit acceptance.

